

Southern Pump Services

Engineering Limited

Specialist in Foul & Storm Water Pumping Stations
Installation | Maintenance | Service

STANDARD KIOSK SPECIFICATION DETAILS

Southern Pump Services Engineering Limited kiosks are manufactured from 2mm-zintec sheet steel to BS6687-1968 (*chromate washed -substrate BS1449 -2.5 microns*), the kiosks are press formed and welded construction to IP55 of BS5490 to give good earth continuity and are finished to the following paint specification:-

- Degrease and clean to remove dust
- One coat of 2 pack etching primer
- Air-dry for 1 hour
- Two coats of pure polyester powder paint to give minimum dry film thickness of 50 microns
- Stove at 180° for 45 minutes

Color is green reference RAL 6005 textured and are fitted with the following equipment as standard

- Two Kiosk lifting brackets
- Wooden backboard
- 14mm floor fixings
- Door stays
- Flush 7mm triangular locks
- Door brackets to facilitate the fitting of a yale lock
- Full height unistruts at rear of each section
- Internal hinges
- Earthling points

The following extras can be fitted as an extra option: -

- Ventilation lovers
- 'Cat Flap' for generator connection
- Anti condensation heater and thermostat
- Plinth

We also provided other materials of construction (314 and 316) stainless steel and different sizes, contact us for further details